

# Canquest Flooring

Technical Specifications	Birch
<b>Width</b> <b>Length</b> <b>Weight (kg/m<sup>2</sup>)</b> <b>Thickness</b> <b>Box per sqm.</b> <b>Pallets</b> <b>Qty per 20' container</b> <b>Qty per 40' container</b> <b>Bevel</b> <b>Hardness (Janka)</b> <b>Waste</b> <b>Moisture</b> <b>Recommended</b> <b>Relative humidity</b> <b>Finish</b>  <b>Installation</b> <b>Warranty</b> <b>Wrapping</b>	83mm/90mm/125mm/148mm 300mm - 1800mm 11.9 15mm/18mm/20mm/22mm 2.1m <sup>2</sup> 104.05m <sup>2</sup> 10 pallets 18 pallets Micro bevel 1260 lbf A 5% margin for error and imperfection is an accepted industry standard. Content between 6% to 8% 37% to 45% 7 layers of scratch resistance lacquer 7 layers of UV Oil White Oil Nail down and Floating Method 10 years against all manufacturing defects: see warranty leaflet Polystyrene membrane
<b>Grades</b>	<b>Premier:</b> Knots free, variation in color from brown to clear. <b>Second and Better:</b> Mixture of Premier and Natural grades. <b>Natural:</b> Variation in coloring from very dark to light tones. Mineral streaks accepted. Sound knots accepted.