

Technical Specifications	Engineered Collection
Width	90 mm / 125 mm / 148 mm / 189 mm
Length	600 - 1800 mm
Box per Sqm.	2.15
Thickness	14 mm / 15 mm
Wear Layer	3 mm / 4 mm / 5 mm
Composition	1 strip / 3 ply
Planks / Box	6 (2,11 m ²)
Box / Pallet	50 (105, 5 m ²), 60 (126, 6 m ²)
Pallets / 20' Ctr	(6 x 50) + (6 x 60), 1392, 60 m ²
Pallets / 40' Ctr	(12 x 50) + (12 x 60), 2785, 20 m ²
Bevels	Micro bevel
Waste	A ± 5% margin for error accepted as per industry standard
Moisture	Content between 6% to 8%
Recommended Relative Humidity	37% to 60%
Finish	7 layers of UV matt lacquer, 7 layers of UV Oil, White Oil
Installation	Nail down, Glue down, Floating method
Warranty	10 years against all manufacturing defects; see warranty leaflet
Wrapping	Polystyrene membrane
Grains (cuts)	Plain Sawn, Rift Sawn
Grades	<p>Premier: Knots free, variation in colour from brown to clear.</p> <p>Second and Better: Mixture of Premier and Natural grades</p> <p>Natural: Variation in colouring from very dark to light tones. Mineral streaks accepted. Sound knots accepted.</p>