

Technical Specifications	Parquet Collection
Width	190 mm
Length	2200 mm
Box per Sqm.	2.89
Thickness	14 mm
Wear Layer	3.6 mm
Composition	3 strip / 3 ply
Planks / Box	2.89 m <sup>2</sup>
Box / Pallet	50 (105, 5 m <sup>2</sup> ), 60 (126, 6 m <sup>2</sup> )
Pallets / 20' Ctr	(6 x 50) + (6 x 60), 1392, 60 m <sup>2</sup>
Pallets / 40' Ctr	(12 x 50) + (12 x 60), 2785, 20 m <sup>2</sup>
Bevels	Micro bevel
Waste	A ± 5% margin for error accepted as per industry standard
Moisture	Content between 6% to 8%
Recommended Relative Humidity	37% to 60%
Finish	7 layers of UV matt lacquer, 7 layers of UV Oil, White Oil
Installation	Nail down, Glue down, Floating method
Warranty	10 years against all manufacturing defects; see warranty leaflet
Wrapping	Polystyrene membrane
Grains (cuts)	Plain Sawn, Rift Sawn
Grades	<p><b>Premier:</b> Knots free, variation in colour from brown to clear.</p> <p><b>Second and Better:</b> Mixture of Premier and Natural grades</p> <p><b>Natural:</b> Variation in colouring from very dark to light tones. Mineral streaks accepted. Sound knots accepted.</p>