

Canquest Flooring

Hardwood & Engineered

TECHNICAL DATA SHEET

CUSTOM COLLECTION - Design Tile



100% Natural



Custom stained



Hand-scraped



T&G assembly system

Wood Grading Guide



Rustic/Natural: Variation in coloring from very dark to light tones. Mineral streaks accepted. Sound knots accepted.

| | |
|---------------------------------|---|
| COLLECTION | Custom Oak |
| DIMENSIONS | |
| Width | 600 mm |
| Length | 600 mm |
| Thickness | 15 mm |
| Wear Layer | 4 mm |
| Bevels | Micro-bevel |
| Box per sq.m | 2.82 m ² |
| Pallets | 104.5 m ² |
| Qty per 20' Container | 10 pallets |
| APPEARANCE | |
| Composition | Single Strip |
| Finish | 7 layers of scratch resistance lacquer, 7 layers of UV Oil, White Oil |
| PROPERTIES | |
| Hardness (Janka) | 1010 lbf |
| Waste | A +/-5% margin for error and imperfection is an accepted industry standard. |
| Moisture Content | Content between 6% to 8% |
| Relative Humidity (recommended) | 37% - 45% |
| Installation Method | Glue-down, Sikabond Acoustic |
| Grains | Plain Sawn |
| WARRANTY | |
| Commercial | Warranty is granted for a period of 5 years in normal use, maintenance, humidity and temperature conditions. |
| Residential | Warranty is granted for a period of 10 years in normal use, maintenance, humidity and temperature conditions. |

Custom Design Samples

